

1	2	3	4	5	6	7	8	9	10						
1										1					
2										2					
3	一体机性能参数Performance parameters with Drive									3					
	参数项Parameter item		单位Unit	参数值Parameter values											
	动力电源Power supply		VDC	48											
	逻辑电源Logic power		VDC	24											
	额定功率Rated Power		W	400											
	额定电流Rated Current		A	10											
	额定转矩Rated Torque		N.m	1.27											
4	额定转速Rated Speed		rpm	3000						4					
	最大电流Maximum current		Arms	33.9											
	最大转矩Maximum torque		N.m	3.81											
	最大转速Maximum speed		rpm	4000											
	转动惯量Rotational inertia		kg.cm2	0.31											
	最大径向力Radial force Max		N	180											
	最大轴向力Axial force Max		N	90											
5	重量Weight		kg	/						5					
	绝缘等级Insulation Class		/	F											
	防护等级Protection Degree		/	IP65											
	工作制Working system		/	S3											
	工作环境温度Working Temperature		/	-20~40℃											
6										6					
7	编码器性能参数Encoder performance parameters									7					
	参数项Parameter item			参数值Values											
	类型Type			绝对值式单圈磁编 (Magnetic single-turn absolute encoder)											
	分辨率Resolution			S17bit											
8													8		
	未注线性公差 Undeclared linear tolerance							批准Approve			料号Part No	3110400177		产品外形图Product Outline Drawing	
	0.5~3			±0.2				标准化Standard			型号Model	iSMRG0-040-DMAX-AA-000-D000		Kinco步科 步科股份：688160 The copyright of this drawing belongs to our company and unauthorized dissemination is prohibited. 页码Page NoSheet 2 Of 2A2	
	>3~6			±0.3				工艺Technique			版本Version	V1.0			
	>6~30			±0.5				审核Check			比例Scale	1: 1			
	>30~120			±0.8	V1.0 /	原始版本	新发布	设计Design	FP	2025/10/22	投影法 Projection methods				
	>120~400			±1.2	VER Mark	版本记录Version record	归档方式ECN No	归档日期Date	评审Review	姓名Names	日期Data				
1	2	3	4	5		6		7		8		9		10	A

一体机性能参数Performance parameters with Drive		
参数项Parameter item	单位Unit	参数值Parameter values
动力电源Power supply	VDC	48
逻辑电源Logic power	VDC	24
额定功率Rated Power	W	400
额定电流Rated Current	A	10
额定转矩Rated Torque	N.m	1.27
额定转速Rated Speed	rpm	3000
最大电流Maximum current	Arms	33.9
最大转矩Maximum torque	N.m	3.81
最大转速Maximum speed	rpm	4000
转动惯量Rotational inertia	kg.cm2	0.31
最大径向力Radial force Max	N	180
最大轴向力Axial force Max	N	90
重量Weight	kg	/
绝缘等级Insulation Class	/	F
防护等级Protection Degree	/	IP65
工作制Working system	/	S3
工作环境温度Working Temperature	/	-20~40℃

编码器性能参数Encoder performance parameters	
参数项Parameter item	参数值Values
类型Type	绝对值式单圈磁编 (Magnetic single-turn absolute encoder)
分辨率Resolution	S17bit

未注线性公差 Undeclared linear tolerance						批准Approve			料号Part No	3110400177	产品外形图Product Outline Drawing	
0.5~3	±0.2					标准化Standard			型号Model	iSMK60-040-DMAX-AA-000-D000	 步科股份：688160 The copyright of this drawing belongs to our company and unauthorized dissemination is prohibited.	
>3~6	±0.3					工艺Technique			版本Version	V1.0		
>6~30	±0.5					审核Check			比例Scale	1: 1		
>30~120	±0.8	V1.0	/	原始版本	新发布	设计Design	FP	2025/10/22	投影法 Projection methods		页码Page No	Sheet 2 Of 2
>120~400	±1.2	VER	Mark	版本记录Version record	归档方式ECN No	归档日期Date	评审Review	姓名Names	日期Data		A2	