









1	2	3	4	5	6	7	8	9	10	
1	转向电机接口名称 Steering Motor Interface Name		行走电机接口名称 Travelling Motor Interface Name						1	
	引线名称 Lead Name	引线号 Pin No	信号定义 Defintion	引线颜色 Colour	线径 Wire Diameter	连接器型号 Connector Models	备注 Remarks			
2	24+I/O	1	DI2	/	/	 Pin7 Pin8 Pin1 Pin2 胶壳: X2026WV-2x4B-NOSN				
		2	DO1	/						
		3	DI1	/						
		4	COM0	/						
		5	/	/						
		6	COM1	/						
		7	24VS	/						
		8	GNDS	/						
3	120R	1	/	/	/	 Pin2 Pin1 Pin4 Pin3 胶壳: A2006WVB-2x2P				
		2	120-R2	/						
		3	/	/						
		4	120-R1	/						
	Can	1	CAN-L	/		 Pin2 Pin1 Pin4 Pin3 胶壳: A2006WVB-2x2P				
		2	CAN-H	/						
		3	CAN-L	/						
		4	CAN-H	/						
4	485	1	485B	/		 Pin2 Pin1 Pin4 Pin3 胶壳: A2006WVB-2x2P				
		2	485A	/						
		3	485B	/						
		4	485A	/						
	SEN	1	GND	/		 Pin2 Pin1 Pin4 Pin3 胶壳: A2006WVB-2x2P				
		2	24V	/						
		3	DI3	/						
		4	/	/						
5	BAT	1	BAT-	/	/	 Pin1 Pin2 胶壳: X2011WV-02A-NOSN	额定电池电压: 3.6V			
		2	BAT+	/						
	PWR1	1	DC-	/	/	 Pin2 Pin1 端子型号: XT30UPB-M				
		2	DC+	/						
6	PWR2	1	DC-	/	/	 Pin1 Pin2 端子型号: XT30UPB-M				
		2	DC+	/						
7									7	
8									8	
1	2	3	4	5	6	7	8	9	10	
</										

